



G-FORCE™ II 4240 KA-DD

IDEAL FOR REMODELING & PROPERTY MAINTENANCE CLEANING

100% HEAVY-GAUGE ALUMINUM FRAME

- > Up to 40% lighter than steel frames
- > Corrosion resistant to water and chemicals
- > Standard on all Graco models

KOHLER® ENGINE

- > Reliable, powerful & easy-to-start

RELIABLE, AR TRIPLEX PLUNGER WATER PUMP

DIRECT DRIVE

- > Compact design with fewer components and lighter weight
- > Pump is connected directly to the drive shaft of the engine
- > Pump rpm matches that of the engine (usually around 3500 rpm)

EZ START PRESSURE RELIEF FOR EASIER STARTING

- > Standard Graco feature
- > Allows water bypass pump to eliminate pressure build-up in the system
- > No need to pull the gun trigger while starting the washer



TECHNICAL SPECIFICATIONS

PART NUMBERS: FOR EURO VERSION (230 V)		25N640
Engine	Kohler ch440	
Transmission	Direct	
Max. Working pressure - bar (psi)	290 (4200)	
Flow - lpm (gpm)	15.14 (4)	
Gun – cm (in)	Professional grade gun 91 cm (36") wand	
Water pump	Ar, triplex plunger pump	
Unloader type	Ez start, adjustable pressure - integrated into pump	
Easy start pressure relief	✓	
Pressure gauge	✓	
Hose	0.95 cm (3/8") x 15 m (50 ft) non-marking with Quick Connects	
Tips	4	
0°- 15°- 25°- 40°	✓ - ✓ - ✓ - X	
Chemical tip	✓	
Weight - kg (lbs)	47.6 (104)	

ACCESSORIES



GUNS

- > 244785 G-FORCE gun only (345 bar)
- > 244779 G-FORCE gun 50 cm (345 bar)
- > 244784 G-FORCE gun 91 cm (345 bar)

HOSE REELS & HOSES

- > 16X664 Hose reel kit, 30 m capacity (345 bar)
- > 244783 Hose 3/8" x 15 m Quick Disconnect (290 bar)

WET SAND BLASTING KIT

- > 244766 Sandblasting kit (380 bar)
Fittings, couplers, clamps, adapters, housing sealant and hose assembly
- > 805321 Sand blasting nozzle (345 bar)

TIPS

- > 198014 Rotating pressure washer tip (360 bar)
- > 198013 Oscillating pressure washer tip (245 bar)



COUPLERS AND ATTACHMENTS

- > 16X680 Gutter cleaning attachment
- > 16X679 Ball valve water shutoff
- > 16X682 G-Force parts box
Tips, plugs, couplers, sockets, thread-seal tape and o-rings
- > 287643 Gardena® water connection adapter (brass)

FLUIDS

- > 246377 Pump oil, 1 liter, for triplex plunger (pumps only)
- > 117784 Pump oil, 0.133 liter, for radial axial (pumps only)

ORIFICE SIZE	0°	15°	25°	40°	SET OF 4 TIPS (0°-15°- 25°- 40°)
2.7	805591	805592	805593	805594	-
3.0	805535	805536	805537	805538	244768
3.5	805539	805540	805541	805542	244769
3.7	805595	805596	805597	805598	-
4.0	805543	805544	805545	805546	800708
4.5	805547	805548	805549	805550	800709
5.0	805551	805552	805553	805554	800710
5.5	805555	805556	805557	805558	-
	Chemical Tip				805634